

AutoFill GX

Application

- Fully automated gas filling solutions for the medical, consumer, industrial and special gas industry

Connections

- Electric: 110 / 240V, 50 / 60Hz, ~100W, single-phase
- CO₂: Customer furnished
- CGA 320 / DIN 477-Nr. 6
- Optional as required

Options

- Additional weight scale (Filltech Add-on, e.g.) with valve and connections for filling small cylinders up to 6 kg fill weight
- Barcode reader, printer and communication interfaces (i.e. TCP/IP)
- Vacuum valve with process-integration

Standards

- Module AI in accordance with RL 97/23/EG PED
- DIN/ISO 9001 and ISO 22000
- Conversions to AD 2000



Highlights

- One-stop-station for all necessary handling: emptying, cleaning, filling, weighing, leakage control, sealing and shielding
- Implementation at your premises
- 24/7 Back-up support available
- General capacity: 1000 CO₂ cylinders/hour
- IT-integration with your system
- Track & Trace
- Ergonomic approach

Weight Scales and Controls

- Digital, freely programmable SysTec IT 8000 industrial weighing terminal
- 999 storable cylinder types (PLU)
- Automatic filling process, manually operated solenoid relief valve
- Monitoring of fill weight, integrated tare weight control
- Enhanced software, i.e. topfilling (only the fill parameter must be set, all other parameters are ready)
- Remote online maintenance possible
- Easy to integrate with different IT solutions